



PATENT ABSTRACTS OF JAPAN

(11) Publication number: 09246037 A

(43) Date of publication of application: 19.09.1997

(51) Int. Cl. H01F 6/00

(21) Application number: 08075386

(22) Date of filing: 06.03.1996

(71) Applicant: TOSHIBA CORP

(72) Inventor: KAWAI MASAMICHI

(54) SUPERCONDUCTING MAGNET EQUIPMENT

(57) Abstract:

PROBLEM TO BE SOLVED: To decrease current density in the inner periphery, and decrease magnetic field, by forming the section of a superconducting coil in a trapezoid wherein the outer peripheral side is longer than the inner peripheral side.

SOLUTION: The section of a superconducting coil 1 is formed in a trapezoid wherein the outer peripheral side 5 of the superconducting coil 1 is longer than the inner peripheral side 6 of the coil 1. As to the maximum empirical magnetic field of the innermost periphery, the strength of magnetic field is reduced by about 10%, on account of the trapezoidal form. Character-

istics of the superconducting coil 1 are defined by the maximum empirical magnetic field. As a result, when the maximum empirical magnetic field is reduced, the load factor of a superconducting wire is reduced by that amount, and the margin reaching the quenching is increased. Thereby a stable superconducting coil is obtained, and the quenching phenomenon is made hard to occur.

COPYRIGHT: (C)1997,JPO

